



FEED-THROUGH Spring Clamp Terminals

These terminal blocks offer a time saving alternative to the popular screw clamp connection. They can be mounted on 35 mm DIN rails. Insulated push-in type jumpers offer a quick and shock proof solution for most cross-connection applications.



Terminal Width	5 mm	6 mm	8 mm
Height x Length	36 x 58 mm	42 x 65 mm	45 x 72 mm
Stripping Length	9 mm	9 mm	12 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 spring clamps & 2 slots for interconnection	2 spring clamps & 2 slots for interconnection	2 spring clamps & 2 slots for interconnection
Approvals	C SP US VDE E220514	C SP US VDE E220514	C SP US VDE E220514
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG	22-12AWG 0.5-4 sq.mm 22-12 AWG	22-8AWG 0.5-8sq.mm 22-8AWG
Voltage Rating	600 V 750 V 600 V	600 V 750 V 600 V	600 V 750 V 600 V
Current Rating	20 A 24 A 20 A	25 A 32 A 25 A	50 A 41 A 50 A

MULTI-CONNECTION Spring Clamp Terminals

Altech Multiple connection Spring Clamp terminals offer a reliable solution for problems posed by multiple voltage connections. The terminal eliminates conventional method of cross connection / looping, saving additional space.

The terminals provide of further multiplication connections through bridging. The Multiple Connection Terminal Blocks can even be bridged to Standard Feed Through Spring Clamp Terminal Block of respective wire size (CSC2.5T / CSC4T / CSC6T).

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSC2.5T	100	CSC4T	100	CSC6T	50
End Plate	EPCSC2.5T	50	EPCSC4T	50	EPCSC6T	50
Partition Plate	PPCSC2.5T	50	PPCSC4T	50	PPCSC6T	50
DIN Rail for ordering information refer to page 62						
End Stop for ordering information refer to page 63	CA702 50 CA802 50		CA702 50 CA802 50		CA702 50 CA802 50	
Jumpers Adjacent Alternate	CA801/1 100 CA801/1-3 100		CA801/2 100 CA801/2-3 100		CA801/3 100 CA801/3-3 100	
Push in type wire jumper	CA901/1 100		CA901/2 100		CA901/3 100	
Marking Tags (MT Type)	MT5 100		MT6 100		MT8 100	



COLOR BLOCKS (other than grey standard)

When ordering please add color suffix to Cat. No.



Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB






CSC10T	CSC2.5T1-2	CSC2.5T2-2	CSC4T1-2
			
CE	CE	CE	CE
10 mm	5 mm	5 mm	6 mm
50 x 75 mm	36 x 74 mm	36 x 90 mm	42 x 85 mm
12 mm	9 mm	9 mm	9 mm
Polyamide 6.6	Polyamide 6.6	Polyamide 6.6	Polyamide 6.6
2 spring clamps & 2 slots for interconnection	3 spring clamps & 2 slots for interconnection	4 spring clamps & 2 slots for interconnection	3 spring clamps & 2 slots for interconnection
  	  	  	  
16-6 AWG 1.5-10 sq.mm. 16-6AWG	22-14 AWG 0.5-2.5 sq.mm. 22-14 AWG	22-14 AWG 0.5-2.5 sq.mm. 22-14 AWG	22-12 AWG 0.5-4 sq.mm. 22-12 AWG
600V 800V 600V	600V 750V 600V	600V 750V 600V	600V 750V 600V
65 A 57 A 65 A	20A 24 A 20 A	20A 24 A 20 A	25A 32 A 25 A

Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
CSC10T	100	CSC2.5T1-2	100	CSC2.5T2-2	50	CSC4T1-2	50
EPCSC10T	50	EPCSC2.5T1-2	50	EPCSC2.5T2-2	50	EPCSC4T1-2	50

			
CA702 50 CA802 50	CA702 50 CA802 50	CA702 50 CA802 50	CA702 50 CA802 50
CA801/4 100	CA801/1 100 CA801/1-3 100	CA801/1 100 CA801/1-3 100	CA801/2 100 CA801/2-3 100
	CA901/1 100	CA901/1 100	CA901/2 100
MT10 100	MT5 100	MT5 100	MT6 100

*UL& CSA pending.

	CSC4T2-2			CSC6T1-2			ADL2.5		
									
	CE			CE			CE		
Terminal Width	6 mm			8 mm			5 mm		
Height x Length	42 x 105 mm			45 x 94 mm			50 x 79.5 mm		
Stripping Length	9 mm			12 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6			Polyamide 6.6		
Type of Connection	4 spring clamps & 2 slots for interconnection			3 spring clamps & 2 slots for interconnection			4 spring clamps & 4 slots for interconnection		
Approvals	  			  			  		
Wire Range	22-12 AWG	0.5-4 sq.mm.	22-12 AWG	22-8 AWG	0.5-6 sq.mm.	22-8 AWG	22-14 AWG	2.5 sq.mm.	22-14 AWG
Voltage Rating	600 V	750 V	600 V	600 V	800 V	600 V	600 V	500 V	600 V
Current Rating	25 A	32 A	25 A	50 A	41 A	50 A	20 A	24 A	20 A
Terminal Block	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.		Cat. No.	Std. Pk.	
	CSC4T2-2	50		CSC6T1-2	50		ADL2.5	50	
End Plate 	EPCSC4T2-2	50		EPCSC6T1-2	50		EPADL2.5	50	
DIN Rail for ordering information refer to page 62									
End Stop for ordering information refer to page 63 	CA702	50		CA702	50		CA702	50	
	CA802	50		CA802	50		CA802	50	
Jumpers Adjacent Alternate 	CA801/2	100		CA801/3	100		CA801/1	100	
	CA801/2-3	100		CA801/3-3	100		CA801/1-3	100	
Push in type wire jumper 	CA901/2	100		CA901/3	100		CA901/1	100	
Marking Tags (MT Type) 	MT6	100		MT8	100		MT5	100	

*UL & CSA pending.

Spring Clamp Fuse Terminal Blocks



Altech offers 'Screwless' Spring Clamp Fuse Terminal Blocks.

The terminal has a moving type hinged carrier that has specially designed space for cartridge type glass fuse of size Ø 5 x 20 or Ø 5 x 25 mm. The fuse can be engaged or disengaged by the movement of the carrier.

Cross connection is possible with specially designed push-in type jumpers.

ASF4

ASF4(L)*



Terminal Width	8 mm			8 mm		
Height x Length	60 x 80 mm			60 x 80 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 spring clamps & 2 slots for interconnection			2 spring clamps & 2 slots for interconnection		
Type of fuse used	Ø5x20, Ø5x25mm			Ø5x20, Ø5x25mm		
Fusion Voltage				24V AC/DC, 48V AC/DC 110V AC/DC, 220V AC		
Approvals						
Wire Range	22-10 AWG 0.5-4 sq.mm 22-10 AWG			22-10 AWG 0.5-4 sq.mm 22-10 AWG		
Voltage Rating	600 V 500 V 600 V			600 V 500 V 600 V		
Current Rating	8 A 6.3 A 8 A			8 A 6.3 A 8 A		



COLOR BLOCKS

(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB

	Cat. No.	Std. Pk.		Cat. No.	Std. Pk.
Terminal Block	ASF4	100		ASF4(L)*	100
End Plate	EPASF4	50		EPASF4	50
DIN Rail for ordering information refer to page 62					
End Stop for ordering information refer to page 63	CA702 CA802	50 50		CA702 CA802	50 50
Insulated Jumper (2 pole)	CA801/7	100		CA801/7	100
Marking Tags (MT Type)	MT8	100		MT8	100

¹ UL & CSA pending.

* Add required voltage to part number as a suffix. i.e. ASF4(L)/24 for 24V AC/DC.


Spring Clamp Ground (Earth) Terminal Blocks

Altech offers 'Screwless' Spring Clamp Ground Terminal Blocks. Specially designed alloy feet helps in achieving very low contact resistance and vibration proof grounding.


CSCG series terminals can be mounted on Din 35 rail along with other terminal blocks of CSC series. The terminal block profile matches with that of CSC terminal block of same wire size.

Special features of CSCG terminal blocks are:


- Vibration proof grounding
- Very low contact resistance because of special alloy feet
- Drop-on grounding connection
- Spring clamp to accept solid and stranded wire



CSCG2.5T



CSCG4T



Terminal Width	5 mm	6 mm
Height x Length	36 x 58 mm	42 x 65 mm
Stripping Length	9 mm	9 mm
Insulation Material	Polyamide 6.6	Polyamide 6.6
Type of Connection	2 spring clamp connection, grounding through alloy feet	2 spring clamp connection, grounding through alloy feet
Approvals	  	  
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG	22-12 AWG 0.5-4 sq.mm 22-12 AWG
Voltage Rating	800 V	800 V
Current Rating	24 A	32 A

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSCG2.5T	100	CSCG4T	100
DIN Rail <i>for ordering information refer to page 62</i>				
Marking Tags (MT Type) 	MT5	100	MT6	100

*UL & CSA pending.

	CSCG6T	CSCG10T								
										
										
Terminal Width	8 mm	10 mm								
Height x Length	45 x 72 mm	50 x 75 mm								
Stripping Length	12 mm	12 mm								
Insulation Material	Polyamide 6.6	Polyamide 6.6								
Type of Connection	2 spring clamp connection, grounding through alloy feet	2 spring clamp connection, grounding through alloy feet								
Approvals	  	  								
Wire Range	22-8 AWG 0.5-6 sq.mm 22-8 AWG	16-6 AWG 0.5-10 sq.mm 16-6 AWG								
Voltage Rating	800 V	800 V								
Current Rating	41 A	57 A								
Terminal Block	<table><tr><th>Cat. No.</th><th>Std. Pk.</th></tr><tr><td>CSCG6T</td><td>50</td></tr></table>	Cat. No.	Std. Pk.	CSCG6T	50	<table><tr><th>Cat. No.</th><th>Std. Pk.</th></tr><tr><td>CSCG10T</td><td>50</td></tr></table>	Cat. No.	Std. Pk.	CSCG10T	50
Cat. No.	Std. Pk.									
CSCG6T	50									
Cat. No.	Std. Pk.									
CSCG10T	50									
DIN Rail <i>for ordering information refer to page 62</i>										
Marking Tags (MT Type)	MT8 100	MT10 100								

*UL & CSA pending.

Panel Mount Spring Clamp Terminals

Altech "screwless" spring clamp panel mount terminal blocks are an excellent solution for extremely compact wiring applications. These terminal blocks are "add-on" type and can be combined to form multi-pole assemblies. The stacked assembly is fitted with mounting end sections on both ends for easy installation on to the panel.

The terminal has marker holding recesses on three sides to accept marking tags. Cross connection can be achieved with the aid of insulated jumpers.

The CSCP2.5T2 panel mount terminal blocks have two connection points on each side all with the same potential. The terminals provide possibility of further multiplication through jumpering.



CE

CE

Terminal Width	5 mm			10 mm		
Height x Length	27 x 35 mm			27 x 35 mm		
Stripping Length	9 mm			9 mm		
Insulation Material	Polyamide 6.6			Polyamide 6.6		
Type of Connection	2 spring clamp connections			4 common spring clamp connections		
Approvals	 US   US			 US   US		
Wire Range	22-14 AWG 0.5-2.5 sq.mm 22-14 AWG			22-14 AWG 0.5-2.5 sq.mm 22-14 AWG		
Voltage Rating	600 V 750 V 600 V			600 V 750 V 600 V		
Current Rating	20 A 24 A 20 A			20 A 24 A 20 A		

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Terminal Block	CSCP2.5T	100	CSCP2.5T2	100
End Section (set of left and right) 	EPCSCP2.5T	50	EPCSCP2.5T	50
Insulated Jumper (2 pole) 	CA803/1	100	CA803/1	100
Operating Tool	SCA2-5	1	SCA2-5	1
Marking Tags (MT Type) 	MT4	100	MT3	100




COLOR BLOCKS



(other than grey standard)

When ordering please add color suffix to Cat. No.

Example: CTS2.5U-N/R

Color	Ordering Suffix
Red	R
Blue	BU
Black	BL
Orange	O
Green	G
Yellow	Y
White	W
Beige	BG
Dark Brown	DB





Custom Assemblies Available

- Most competitive in industry
- Made to your specifications
- Large inventory of parts
- Variety of colors available
- Custom marking tags
- Up to 6' custom assemblies

