



E3FA-LP22

Photoelectric sensor, M18 threaded barrel, plastic, red LED, background suppression, 200 mm, PNP, Light-ON/Dark-ON, M12 connector

Specifications

Shape	Cylindrical axial
Sensing method	Background suppression
Sensing distance	200 mm
Setting method	Fixed
Connection method	Connector M12
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	0.5 ms
Material housing	ABS
Thread size	M18
Product Length (unpacked)	45 mm
Type of light	Polarity free red light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

Accessories



E39-L182

E3FA/R flush mounting bracket



E39-L183

M18 L-type mounting bracket, stainless steel (SUS304)

Related products



M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

Downloads

CAD Library



E3FA Cylindrical Photoelectric Sensors Brochure

EN PDF 9.01 MB



E3FA- Instruction Manual

EN PDF 372 KB



E3FA/E3RA/E3FB/E3RB Photoelectric Sensors Datasheet

EN PDF 6.32 MB



EAC Mark removal Discontinuation Notice

EN PDF 221 KB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 24 April, 2025. [Click here for terms of use.](#)

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU